

## Enhance 2-1 Alternating System

### 2-1 Alternating System



#### Main Feature:

- \* 5" air cell overlay
- \* 2-1 alternation and static
- \* Micro low air loss
- \* Visual and audio low pressure alarm
- \* Dial comfort setting control
- \* Modularized design for air mattress
- \* Integrated power cable retainer
- \* High vapor permeable and quilted nylon cover
- \* SWL 350lb
- \* Quick CPR deflation within 20 seconds

#### Clinical Considerations:

1 Multiple stage 2, 3 or 4 pressure ulcer

#### Enhance Specification

##### Control Unit

Model Name	<b>Enhance</b>
Model No.	FC-PHR0003
Size (inch)	10.1" (L) x 4.5" (W) x 8.3" (H)
Weight (lbs)	5.1
Cycle Time	10 min
Min Operating Pressure	16 +/- 6mmHg
Max Operating Pressure	32 +/- 6mmHg
Flow-rate	≥4.5 l/min

Rated Voltage	AC 110-120V
Rated Frequency	60 Hz
Fuse Rating	1A 250V
Max Current	0.1A
Classification	Class I, Type BF Not AP or AGP type
Operation Temperature	15°C (59°F)~ 35°C(95°F)
Operation Humidity	30% ~ 75%
Mode of Operation	Continuous
Standard	IEC 60601-1, CAN/CSA C22.2 No. 601.1, IEC 60601-1-2

Mattress

Model No	FM-PHR0003
Size (inch)	36" (W) x 80" (L) x 5" (H)
Weight (lbs)	16.7
Cell Number	20 cells
Cells Material	Nylon coated with PU
Cover Type	Zipper cover
Cover Material	Nylon woven fabric w/ PU coating finish
Base Material	Woven Polyester fabric w/ PVC backing