

PRIUS Salute Alternating System

PRIUS Salute Alternating System



Main Feature:

- * 8" air cell mattress replacement
- * 3-1 alternation and static
- * Micro low air loss
- * Visual and audio low pressure alarm
- * Dial comfort setting control
- * Modularized design for air mattress
- * Integrated power cable retainer
- * High vapor permeable and quilted nylon cover
- * Happy Heel – mechanical foot section softness adjustment
- * Cell in cell design provides addition protection for upper torso and sacrum during power outage
- * SWL 500lb
- * Quick CPR deflation within 20 seconds

Clinical Considerations:

- * Multiple stage 2, 3 or 4 pressure ulcer

Salute Specification

Control Unit

Model No.	FC-PHR0007
Model Name	Salute
Size (inch) LxWxH	13.5" x 7.3" x 8.3"
Weight (lbs)	7.1
Cycle Time (min)	20 min
Min Pressure	16mmHg +/- 6mmHg
Max Pressure	32mmHg +/- 6mmHg
Flow-rate	≥4.5 l/min

Rated Voltage	110~120 volt
Max Current	0.1 Amp
Fuse Rating	1A 250V
Rated Frequency	60 Hz
Protection Type	Class I, Type BF Not AP/APG Protection
Mode of Operation	Continuous
Environment (Temperature)	Operation: 15°C to 35°C(59°F to 95°F) Storage:5°C to 60°C (41°F to 140°F)
Environment (Humidity)	Operation: 30% to 75% non-condensing Storage: 30% to 75% non-condensing

Mattress

Model No	FM-PHR0005
Size (inch) LxWxH	80" x 36" x 8"
Weight (lbs)	15.4
Cells Number	18 cells
Cells Material	Nylon coated with PU
Cover Material	Nylon woven fabric w/ PU coating finish
Base Material	Woven Polyester fabric w/ PVC backing